



(N)YFAZ PVC Twin Wire

Audio Speaker Cable

transparent



IEC 60228 ; IEC 60332-1-2

RoHS , REACH & CE Directives



Ambient installation T°
C range
0 + 50 °C



Operating temp.
-30 + 70 °C



Storage temperature
range
-20 + 70 °C



Flame retardant
IEC 60332-1



Smoke density

Application

YFAZ speaker transparent cables are flexible, PVC-insulated twin cables designed for Hi-Fi, home cinema, and professional PA systems. Suitable in dry locations for connections in communication

technology, mainly for HIFI applications such as a loudspeaker connecting cable, also used for speakers, in home or in public facilities, but withstand very weak mechanical stresses.

Technical Data Sheet

YFAZ Construction:

Conductor material:

Class 5 Fine stranded bare copper

Core Insulation:

PVC compound TI2 (Polyvinyl chloride)

Laid up parallel, insulated with very soft PVC

Color marking

both conductors are transparent

Flame retardant according to EN 60332-1-2

Technical Data:

Nominal voltage:

U₀/U 300/300 V

Test voltage

2000 V

Capacity

130 pF/m appr.

Temperature range (for flexible use)

-5°C to +70 °C

(fixed installation)

-30°C to +70 °C

Minimum bending radius

6 x Overall Diameter

YFAZ-Audio Speaker cable

Dimensions:

Cable Description	Conductor construction (appr. value) mm	Color	Overall measures (appr. value) mm	Nominal Cable Weight (kg/km)	Packaging m
2 x 0.5	16 x 0.20	transparent	2.4 x 4.7	20-21	100/200
2 x 0.75	24 x 0.20	transparent	2.7 x 5.5	27-28	100/200
2 x 1	32 x 0.20	transparent	2.8 x 5.7	31-33	100/200
2 x 1.5	24 x 0.25	transparent	2.9 x 5.9	37-39	100/500
2 x 2.5	42 x 0.25	transparent	3.6 x 7.4	59-62	100/500
2 x 4	46 x 0.30	transparent	4.2 x 8.5	88-91	100/500



The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.